



NOTE

1. VOLTAGE: TO SPEC
2. FINISH: PAINT TO SPEC
3. INDOOR/OUTDOOR USE
4. LAMPS BY OTHERS

NO.	DESCRIPTION
1	LAMP, SEE TABLE
2	GLOBE, FROSTED POLYCARBONATE
3	REFRACTOR, BOROSILICATE GLASS TYPE III DISTRIBUTION *SEE NOTES FOR OTHER DISTRIBUTION TYPE SPECIFICATIONS*
4	LENS GUARD, .25" ALUMINUM c/w .375" TOP RING
5	LAMPHOLDER, MEDIUM BASE
6	GLOBE FITTER, CAST ALUMINUM
7	CAPACITOR & IGNITOR
8	BALLAST, CORE & COIL
9	BALLAST HOUSING, ALUMINUM
10	LUMINAIRE POST 2"Ø SLIP FITTER
11	WIRE ACCESS PLATE 2"x4" (BY OTHERS)
12	POLE 4"SQ ALUMINUM (BY OTHERS)
13	POLE BASE COVER .125" ALUMINUM (BY OTHERS)
14	BASE PLATE .5" ALUMINUM (BY OTHERS)
15	ANCHOR BOLTS .5"x18.00" ON 8.5"Ø BOLT PATTERN (BY OTHERS)

Maximum Wattage SEE TABLE

When ordering, specify desired VOLTAGE eg: LE\POST-21576-150HPS-120V

*Consult factory for the optional CLEAR ACRYLIC GLOBE

Consult factory for the optional TYPE V GLASS REFRACTOR

Consult factory for the optional TYPE V ALUMINUM LOUVRE

Consult factory for the optional OPAL ACRYLIC GLOBE

GLOBE	MAXIMUM WATTAGE	DIM "A"	DIM "B"
14"	50W	Ø18"	25.375"
16"	100W	Ø20"	27.375"
18"	150W	Ø22"	29.375"
20"	175W	Ø24"	31.375"

TYPE:	PROJECT
-------	---------



LE\POST-21576	
DATE: 97.05.26	SCALE: NTS
DRAWING NO.	L21576R1