




LITE ENERGY ARCHITECTURAL CAGES




DIMENSIONS

Series 500
Surface



Series 600
Surface or Recessed



SPECIFICATIONS

Series 500

Surface

White opal acrylic

White opal polycarbonate

Series 600

Surface or Recessed

White opal polycarbonate

No other lens available

Mounting

Standard Lens

Optional Lens

Maximum Wattage

Compact Fluorescent 2 x CF42TRI

Metal Halide

100w

2 x CF42TRI

150w

SAMPLE CATALOGUE NUMBER: AC501-1XCF26QUAD-120-OA-WH-QTD

AC	MODEL	LAMP SOURCE	VOLTAGE	LENS	COLOUR	OPTION
	501	1 X CF26QUAD	120	OA - Opal Acrylic	WH - White	QTD - Quartz Time Delay
	503	2 X CF26QUAD	277	OP - Opal Polycarbonate	BL - Black	QEM - Quartz Emergency
	506	1 X CF32TRI	347	CA - Clear HI-impact Acrylic	BR - Bronze	EM - Emergency
	602	2 X CF32TRI			MB - Metallic Bronze	
	603	1 X CF42TRI			SI - Silver	
		2 X CF42TRI			RAL - Specify RAL colour no.	
		1 X 50MH				
		1 X 70MH				
		1 X 100MH				
		1 X 150MH				

OPTIONS:

EM - Emergency for CF lamp.

QTD - Quartz Time Delay - HOT/COLD RESTRIKE min. 75w T4 mini-candelabra. Available only for HID products with 100W lamp source or higher.

QEM - Quartz Emergency - must have auxiliary power supply (ie. 120v AC generator)

NOTE: All fixtures are c-CSA-us listed for outdoor locations