



Maximum Wattage **1000W (MH)**

For the Metal Halide wattage option, add wattage and suffix "MH" to Catalogue No. eg: LE\P-25158-**1000MH**

For the 150W "Hot/Cold Re-Strike" option, add suffix "150Q" to Catalogue No. eg: LE\P-25158-400MH\150Q

When ordering, specify desired VOLTAGE eg: LE\P-25158-400MH\150Q-120V

For optional WIRE GUARD use suffix "W" eg: LE\P-25158-400MH\150Q-120V\W

Fixture supplied complete with **REMOTE MOUNTED POTTED BALLAST.**

NOTES:

1. VOLTAGE: TO SPEC
2. FINISH: TO SPEC
3. INDOOR USE
4. LAMPS BY OTHERS

NO.	DESCRIPTION
1	J-BOX (BY OTHERS)
2	CANOPY
3	MOUNTING STRAP 16GA S/C STEEL
4	BALL ALIGNER 45 deg ADJUSTMENT
5	STEM 1/2"NP
6	AIRCRAFT CABLE SAFETY SUPPORT ASSEMBLY
7	STEM COUPLER
8	LAMPHOLDER (MOGUL BASE)
9	SOCKET CUP
10	LAMP, HID (MOGUL BASE)
11	WIRE GUARD OPTIONAL SEE NOTE
12	REFLECTOR HOUSING SUPPORT ASSEMBLY
13	LAMP Q150T4 DC BAY OPTIONAL SEE NOTE
14	REFLECTOR, ALUMINUM
15	HOUSING, .081" ALUMINUM

TYPE:	PROJECT
-------	---------

LE\P-25158



DATE: 01.01.26	SCALE: NTS
DRAWING NO.	L25158R5