



Continuous research and development may require to discontinue or alter a product for improvements, without notice. Consult factory for updated information

Maximum Wattage **UPLIGHT 250MH**
DOWNLIGHT 4xCF26QUAD

For the CF & MH wattage option, add wattage and suffix To Catalogue No.
eg: LE\P-32228-4F13QUAD/250MH

When ordering, specify desired VOLTAGE eg:
LE\P-32228-4F13QUAD\250MH-120V

Fixture supplied complete with REMOTE MOUNTED POTTED BALLAST FOR "HID" AND INTEGRAL "CF" BALLAST for DRY INDOOR INSTALLATION
Consult factory for mounting distance from HID Ballast to Lamp

SEPARATE CIRCUITS SUPPLIED FOR COMPACT FLUORESCENT DOWNLIGHT SYSTEM AND HID UPLIGHT SYSTEM

- NOTES:
1. VOLTAGE: TO SPEC
 2. FINISH: PAINT TO SPEC
 3. INDOOR USE
 4. LAMPS BY OTHERS

NO.	DESCRIPTOIN
1	SAFETY SUPPORT A/C CABLE HARNESS
2	SAFETY SUPPORT 1/4-20 ROD (BY OTHERS)
3	J-BOX (BY OTHERS)
4	CANOPY
5	SUPPORT BRACKET ASSEMBLY
6	BALL ALIGNER 45° ROTATION
7	STEM 3/4NP
8	STEM HUB
9	YOKE 1/4NP
10	LENS, CLEAR TEMPERED GLASS
11	LENS, ACRYLIC c/w SANDBLASTED EXTERIOR & FAUX ALABASTER FINISH
12	LENS GUARD ASSEMBLY, ALUMINUM
13	REFLECTOR, SPECULAR ALUMINUM
14	BALLAST 2F13QUAD ELECTRONIC (2)
15	LAMPHOLDER
16	LAMP F13QUAD DOWNLIGHT (4)
17	LAMPHOLDER, MOGUL BASE
18	LAMP, HID UPLIGHT (E28)
19	LENS FRAME SUPPORT ASSEMBLY
20	A/C CABLE ASSEMBLY, ADJUSTABLE (4)
21	STEM SLEEVE
22	ELECTRICAL TRAY c/w STANDARD SILVER PAINT FINISH

TYPE: PROJECT:

LE\P-32228
4xCF13QUAD/100MH



DATE: 06.09.18 SCALE: NTS
DRAWING NO. L32228R3